

Fichier de configuration

.zshrc

```
# Lines configured by zsh-newuser-install
HISTFILE=~/.zsh_history
HISTSIZE=1000
SAVEHIST=1000
setopt autocd beep nomatch
unsetopt appendhistory extendedglob notify
bindkey -v
# End of lines configured by zsh-newuser-install
# The following lines were added by compinstall
zstyle :compinstall filename '/home/maxime/.zshrc'

autoload -Uz compinit
compinit
# End of lines added by compinstall

# UNIX variables.
# $PATH taken from the OpenBSD 5.3 default ~/.profile file.
PATH=$HOME/bin:/bin:/sbin:/usr/bin:/usr/sbin:/usr/X11R6/bin:/usr/local/
bin:/usr/local/sbin:/usr/games:.
#TERM="xterm-color"
VISUAL=/usr/local/bin/vim
EDITOR=/usr/local/bin/vim
PAGER=/usr/bin/less

# OpenBSD specific variables.
PKG_PATH=http://ftp.fr.openbsd.org/pub/OpenBSD/`uname -
r`/packages/`machine` -a`/
CVSROOT=anoncvs@anoncvs.fr.openbsd.org:/cvs

# Prompt.
PS1="%F{cyan}%n%f@%F{green}%m%f %B%F{white}%2d%f%b %% "
#PS2
#PS3
#PS4

# Locale.
LC_CTYPE=fr_FR.UTF-8
LANG=fr_FR.UTF-8

# Working HOME and END keys.
# Taken from <http://zshwiki.org/home/zle/bindkeys>.
# -----
autoload zkbd
function zkbd_file() {
    [[ -f ~/.zkbd/${TERM}-${VENDOR}-${OSTYPE} ]] && printf '%s'
```

```
~/ ".zkbd/${TERM}-${VENDOR}-${OSTYPE}" && return 0
[[ -f ~/.zkbd/${TERM}-${DISPLAY} ]] && printf '%s'
~/ ".zkbd/${TERM}-${DISPLAY}" && return 0
return 1
}

[[ ! -d ~/.zkbd ]] && mkdir ~/.zkbd
keyfile=$(zkbd_file)
ret=$?
if [[ ${ret} -ne 0 ]]; then
    zkbd
    keyfile=$(zkbd_file)
    ret=$?
fi
if [[ ${ret} -eq 0 ]] ; then
    source "${keyfile}"
else
    printf 'Failed to setup keys using zkbd.\n'
fi
unfunction zkbd_file; unset keyfile ret

# setup key accordingly
[[ -n "${key[Home]}" ]] && bindkey "${key[Home]}" beginning-of-
line
[[ -n "${key[End]}" ]] && bindkey "${key[End]}" end-of-line
[[ -n "${key[Insert]}" ]] && bindkey "${key[Insert]}" overwrite-
mode
[[ -n "${key[Delete]}" ]] && bindkey "${key[Delete]}" delete-char
[[ -n "${key[Up]}" ]] && bindkey "${key[Up]}" up-line-or-
history
[[ -n "${key[Down]}" ]] && bindkey "${key[Down]}" down-line-or-
history
[[ -n "${key[Left]}" ]] && bindkey "${key[Left]}" backward-char
[[ -n "${key[Right]}" ]] && bindkey "${key[Right]}" forward-char
# -----

# Colors.

# Completion.

# Key bindings.
alias ll='colorls -GAhF'
```

.zlogin

```
/usr/bin/calendar -A 0 -f /usr/share/calendar/calendar.all
```

Configuration

The function will not be run in future, but you can run it yourself as follows:

```
autoload -Uz zsh-newuser-install
zsh-newuser-install -f
```

```
maxime@save /home/maxime % touch .zshenv .zprofile .zlogout
```

Ordre d'exécution des fichiers de configuration (cf <http://zsh.sourceforge.net/FAQ/zshfaq03.html#I19>) :

- login shell : `.zshenv` ⇒ `.zprofile` ⇒ `.zshrc` ⇒ `.zlogin` ;
- interactive shell : `.zshenv` ⇒ `.zshrc` ;
- `zsh -f` : `.zshenv`.

Bibliographie

- site web officiel : <http://www.zsh.org/>
- Wikipedia : http://en.wikipedia.org/wiki/Z_shell http://fr.wikipedia.org/wiki/Z_Shell
- portail SourceForge : <http://zsh.sourceforge.net/>
- wiki : <http://zshwiki.org/home/>
- introduction : http://zsh.sourceforge.net/Intro/intro_toc.html (1995)
- user guide : <http://zsh.sourceforge.net/Guide/zshguide.html>
- FAQ : <http://zsh.sourceforge.net/FAQ/>
- etc.

From:
<http://www.mouet-mouet.net/doku.php/doku.php/> - **mouet-mouet !**

Permanent link:
<http://www.mouet-mouet.net/doku.php/doku.php/doku.php?id=maxime:openbsd:docs:zsh>

Last update: **2021/10/08 00:17**

