Installation

OpenBSD 5.4 :

```
# pkg_add -iv php-5.3.27 php-fpm-5.3.27 pecl-APC-3.1.9p3 pecl-
memcache-3.0.6p3
```

Fichier de configuration

php.ini

```
max_execution_time = 600
max_input_time = -1

max_input_vars = 10000
memory_limit = 256M

log_errors_max_len = 1024

post_max_size = 128M

upload_max_filesize = 128M


session.save_handler = memcache
session.save_path = "127.0.0.1:11211"
session.use_strict_mode = 1


opcache.enable = 1

opcache.memory_consumption = 128
opcache.interned_strings_buffer = 8
opcache.max_accelerated_files = 4000

opcache.validate_timestamps = 0

opcache.fast_shutdown = 1



allow_url_fopen = Off

disable_functions =
curl_exec,curl_multi_exec,dl,escapeshellcmd,escapeshellarg,exec,ini_set
,parse_ini_file,passthru,pclose,popen,posix_kill,posix_mkfifo,posix_set
```

```
pgid,posix_setsid,posix_setuid,proc_close,proc_get-
status,proc_nice,proc_open,proc_terminate,shell_exec,show_source,set_ti
me_limit,system,virtual

open_basedir = "/opt/www/html:/tmp"


suhosin.request.max_varname_length = 128
suhosin.get.max_name_length = 128
```

php-fpm.conf

```
user = test-default
group = test-default

listen = 127.0.0.1:9000
listen.allowed_clients = 127.0.0.1
pm = dynamic
pm.max_children = 5
pm.start_servers = 2
pm.min_spare_servers = 1
pm.max_spare_servers = 3

pm.status_path = /php-status-default
ping.path = /php-ping-default
ping.response = pong
```

vhost_nginx_for_fpm_pool_monitoring.conf

```
        location ~ ^/php-(status|ping)-default {
                fastcgi_pass    127.0.0.1:9000;
                fastcgi_param   SCRIPT_FILENAME
$document_root$fastcgi_script_name;
                include         fastcgi_params;
                fastcgi_read_timeout       180;
        }
```

Configuration

blah

Bibliographie

- site web officiel : http://www.php.net/ ;
- Wikipedia : / ;
- etc.

From:
http://www.mouet-mouet.net/ - **mouet-mouet !**

Permanent link:
http://www.mouet-mouet.net/doku.php?id=maxime:openbsd:docs:php

Last update: **2021/10/08 00:17**